


















TECHNICAL DATA SHEET ALTRO CLASSIC 25 (X25) ALTRO ATLAS 40 (X40)

Product Description	Decorative, flexible, non-directional PVC Safety Flooring containing Aluminium Oxide granules throughout and Silicon Carbide granules on the surface		
Areas of Use	X25 - Changing rooms, kitchens, bar serveries X40 - machine shops, industry, heavy duty cart areas, chemical processing.		
Support Reinforcement	Non-woven polyester & cellulose glass scrim		
		X25	X40
Thickness		2.5mm	4.0mm
Weight		2.9kg/m ²	4.5kg/m ²
Roll dimensions		2m x 20m - 40m ²	2m x 12.5m -25m ²
Colours		7	5
Warranty		15 years	15 years

Product Approval		EN 13845	Approved	
Water Tightness		EN 13553	Approved	
Classification For Use		EN 685	34 & 43	
Light Fastness		EN 20105-B02	>6	
Sound Insulation		ISO 140-8	5dB (X25)	7dB (X40)
Wear Resistance		EN 660-2	Group T	
Flexibility		EN435	Pass	
Indentation		EN 433	<0.10mm	
Fire Performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B _{fl} s1 >8kW/m ² Pass	
Slip Resistance		TRRL DIN 51130 EN 13845 EN 13893	≥36 Low potential for slip R10 ESf DS	
Chemical Resistance		EN 423	Good *	
Castor Chair Abrasion		EN 425	Pass	
Suitability for Under Floor Heating		EN 12667 (Thermal Conductivity)	Suitable	
Biocidal			Contains integral biocide	

* please contact Altro Technical Services for further information