


















## TECHNICAL DATA SHEET ALTRO STRONGHOLD 30 (K30)

Product Description	Decorative, flexible, non-directional PVC Safety Flooring containing Aluminium Oxide granules throughout and Silicon Carbide, Quartz granules on the surface.		
Areas of Use	Large Kitchens (400+ meals daily), confined kitchens subject to spillage, meat cutting rooms, fast food kitchens and serveries		
Support Reinforcement	Non-woven polyester & cellulose glass scrim		
Total Thickness		EN 428	3.0mm
Weight		EN430	3.4kg/m <sup>2</sup>
Roll dimensions		EN426	2m x 15m - 30m <sup>2</sup>
Colours	12		
Warranty	15 years		

Product Approval		EN 13845	Approved
Water Tightness		EN 13553	Approved
Classification For Use		EN 685	34 & 43
Light Fastness		EN 20105-B02	>6
Sound Insulation		ISO 140-8	10dB
Wear Resistance		EN 660-2	Group T
Flexibility		EN435	Pass
Indentation		EN 433	<0.10mm
Fire Performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B <sub>fl</sub> s1 >8kW/m <sup>2</sup> Pass
Slip Resistance		TRRL DIN 51130 EN 13845 EN 13893	≥50 Low potential for slip (Class C CTE) R12 ESf DS
Chemical Resistance		EN 423	Good *
Castor Chair Abrasion		EN 425	Pass
Suitability for Under Floor Heating		EN 12667 (Thermal Conductivity)	Suitable
Biocidal			Contains integral biocide

\* please contact Altro Technical Services for further information