


















TECHNICAL DATA SHEET ALTRO MARINE 20 (T20/IPT20)

Product Description	Decorative, flexible, non-directional PVC Safety Flooring containing Quartz granules and decorative PVC chip on the surface. This product has a profiled surface		
Areas of Use	Shower and drying areas, swimming pool and whirlpool surrounds, swimming pool changing rooms and other wet areas requiring slip resistance		
Support Reinforcement	Non-woven polyester & cellulose glass scrim		
Total Thickness		EN 428	2.5mm
Weight		EN430	2.5kg/m ²
Roll dimensions		EN426	2m x 20m - 40m ²
Colours	10		
Warranty	7 years		

Product Approval		EN 13845	Approved
Water Tightness		EN 13553	Approved
Classification For Use		EN 685	34 & 43
Light Fastness		EN 20105-B02	>6
Sound Insulation		ISO 140-8	13dB
Wear Resistance		EN 660-2	Group T
Flexibility		EN435	Pass
Indentation		EN 433	<0.10mm
Fire Performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B _{fl} s1 >8kW/m ² Pass
Slip Resistance		TRRL DIN 51130 EN 13845 EN 13893	Low potential for slip R10 ESb DS
Chemical Resistance		EN 423	Good *
Castor Chair Abrasion		EN 425	Pass
Suitability for Under Floor Heating		EN 12667 (Thermal Conductivity)	Suitable
Biocidal			Contains integral biocide

* please contact Altro Technical Services for further information